

Speed Dome Camera



Features

- ◆ Outdoor Endless High Speed Dome
- ◆ 0.01 Lux Extreme Low Light with Day & Night Function
- ◆ Aluminum Body and Poly Carbonate Dome Cover
- ◆ Low Noise DC Motor or Step Motor
- ◆ 27X and 22X Optic Zoom
- ◆ 64 Preset Positions
- ◆ 360° Endless Pan Angle
- ◆ Outdoor Application
- ◆ Support Multi Protocol

Specification

Model	SSD 27X	SSD-35X
Signal Format	PAL/NTSC	
Video Sensor	1/4" Interline Transfer CCD Sony Super HAD	
Effective Pixels	752 (H) X 582 (V)	
Horizontal Resolution	480 TVL	
S/N Ratio	50 dB	
Minimum Illumination	0.01 Lux (Digital Slow Shutter up) / 0.003 Lux (Night Mode)	
Pan/Angle Manual Speed Preset Speed	0°-360° (Endless)	
	More than 0.5°~300°/Sec (Zoom Proportional)	
	300° Sec (Zoom Proportional)	
Tilt/Angle Manual Speed	0~90°	
	More than 120°~1 Sec (Zoom Proportional)	
Baud Rate	1200 bps, 2400bps, 4800bps, 9600bps	
ID (Camera Address)	0~255 address	
Communication	Rs 485	
Operating Temperature	-10° to 50°C	
Body Type	IP 66 with Heater and Cooler	
Power	AC 24V 50/60 HZ 1.5 A	
Weight	Approx 5.5 Kg	
Humidity	<90% (No Heater. No Defroster)	
Dimensions	Φ 235 X 268 mm (H)	
Power Consumption	15w, 25w (with Heater)	